



Specifications and technical data are subject to change without notice.  
Please contact us to confirm relevant information on ordering.

**Shanghai Ebasee Electric Co., Ltd**

Add: No.18, Gutang Rd, Shanghai 201209, China

Tel: +86 21 5032 0898

Fax: +86 21 5032 0828

<http://www.ebasee.com>



APP



CONTROL ELECTRIC

Copy right reserved EBS: NO.2016003



**Ebasee**  
Smart Living Green Ebasee  
Ebasee Ltd., China

## Company Profile

As a leading supplier in the low voltage electrics industry, Shanghai Ebasee Electric Co., Ltd. products have been used for residential, commercial and industrial applications with its quality and service. EBASEE brand is recognized for its quality and reliability in an ever-increasing number of markets worldwide. So far EBASEE products have gained many international approvals, such as **TUV, KEMA, CB, SEMKO, RoHS, CE, and CCC** etc.

With quality raw materials and components supply, all products are manufactured to EBASEE's defined specifications. We have 4 semi-auto production lines, up to date quality control facilities, and well-trained skillful workers. Moreover, with a technical R & D team and fully equipped in-house laboratory, EBASEE factory can carry out efficient new products developing and daily production QC as well.

EBASEE have wide range cooperations with world leading companies in new products developing or OEM, ODM cooperation. Meanwhile we also process industry cooperation on intelligent home products, and work with some university such as Xi'an Jiao Tong University on project solutions. EBASEE is focused on achieving growth through the growth and success of its worldwide partners.

EBASEE, guided by the "market-oriented" philosophy, powered with the "Quick response and flexible supply" capability, can support our worldwide partners to compete against established global players to deliver the most comprehensive and cost-effective products and service in the market.

"Smart life, Green EBASEE"



## Enterprise credit




# EBS1TR-K Thermal Relay



## Specifications

Setting range(A)	0.10-0.16	0.16-0.25	0.25-0.4	0.4-0.63	0.63-1	1-1.6
	1.6-2.5	2.5-4	4-6	5.5-8	7-10	9-13
For contactor	EBS1C-K06/09 EBS1C-09 EBS1C-12 EBS1C-18					
Contactor parameter	Ith=10A,1NO+1NC					



Relay setting range	Fuses to be used with selected relay		Type code
	aM Type(A)	gG Type(A)	
0.1~0.16	0.25	0.5	1TR-K0301
0.16~0.25	0.25	0.5	1TR-K0302
0.25~0.3	0.5	1	1TR-K0303
0.3~0.54	1	1.6	1TR-K0304
0.54~0.8	1	2	1TR-K0305
0.8~1.2	2	6	1TR-K0306
1.2~1.8	4	8	1TR-K0307
1.8~2.6	4	10	1TR-K0308
2.6~3.7	6	16	1TR-K0310
3.7~5.5	8	20	1TR-K0312
5.5~8	10	25	1TR-K0314
8~11.5	16	32	1TR-K0316
0.1~0.16	0.25	0.5	1TR-K0501
0.16~0.25	0.25	0.5	1TR-K0502
0.25~0.3	0.5	1	1TR-K0505
0.3~0.54	1	1.6	1TR-K0504
0.54~0.8	1	2	1TR-K0505
0.8~1.2	2	6	1TR-K0506
1.2~1.8	4	8	1TR-K0507
1.8~2.6	4	10	1TR-K0508
2.6~3.7	6	16	1TR-K0510
3.7~5.5	8	20	1TR-K0512
5.5~8	10	25	1TR-K0514
8~11.5	16	32	1TR-K0516



EBS1TR-K  
3 Pins



EBS1TR-K  
5 Pins