 Specifications and technical data are subject to change without notice.
Please contact us to confirm relevant information on ordering.



MODULAR TERMINAL

Copy right reserved EBS, NO.2016001



Shanghai Ebasee Electric Co., Ltd

Add:No.18, Gutang Rd,Shanghai 201209, China
Tel: +86 21 5032 0898
Fax: +86 21 5032 0828
[http:// www.ebasee.com](http://www.ebasee.com)



APP

Ebasee
Smart Living Green Ebasee
Ebasee Ltd.,China

Company Profile

As a leading supplier in the low voltage electrics industry, Shanghai Ebasee Electric Co., Ltd. products have been used for residential, commercial and industrial applications with its quality and service. EBASEE brand is recognized for its quality and reliability in an ever-increasing number of markets worldwide. So far EBASEE products have gained many international approvals, such as **TUV, KEMA, CB, SEMKO, RoHS, CE, and CCC** etc.

With quality raw materials and components supply, all products are manufactured to EBASEE's defined specifications. We have 4 semi-auto production lines, up to date quality control facilities, and well-trained skillful workers. Moreover, with a technical R & D team and fully equipped in-house laboratory, EBASEE factory can carry out efficient new products developing and daily production QC as well.

EBASEE have wide range cooperations with world leading companies in new products developing or OEM, ODM cooperation. Meanwhile we also process industry cooperation on intelligent home products, and work with some university such as Xi'an Jiao Tong University on project solutions. EBASEE is focused on achieving growth through the growth and success of its worldwide partners.

EBASEE, guided by the "market-oriented" philosophy, powered with the "Quick response and flexible supply" capability, can support our worldwide partners to compete against established global players to deliver the most comprehensive and cost-effective products and service in the market.

"Smart life, Green EBASEE"



Enterprise credit




EBS9TF Transformer



Nomenclature

EBS 9TF - 8 / 8



Application

Applicable to circuit with rated voltage 230V~ and rated frequency 50/60Hz, used to power electric bell of extra low voltage.

Function

- Safe electrical separation between primary and secondary circuit
- Provides extra low voltage up to 24V
- Low temperature rising
- High output accuracy
- Extra overload capacity up to 25% within 24 hours

Technical Parameter

Rated input voltage	230V AC 50/60Hz
Rated output voltage	8, 12, 24V
Rated power output	8VA
Consumption	1.15W
Service period	continuous operating
Pollution class	2
Connection terminals	pillar terminal with clamp
Connection capacity	rigid conductor 10mm ²
Installation	On symmetrical DIN rail Panel mounting